

Technical data

Product information		SPC Click	
Material	100% virgin PVC+Calcium calcite powder		
Overall thickness	8mm		
Plank Size	228x1840mm		
Package	4pcs		
Finish	UV Coating, Semi-matt 6-8 degree		
Emboss	Deep embossing		
Installation	Click system		
Locking System	Välinge 2G-5Gi		
Bevel	Four-sided bevel		
Floor heating installation	Only suitable for underfloor heating		
UNDERLAYMENT INFORMATION			
Material	IXPE		
Thickness	1.5mm (+/- 0.1, unstressed)		
REFERENCE	NORMS	RESULT	
Tolerance of Length	EN ISO 24342	Avg±0.2mm, Max≤0.5mm	
Tolerance of Width	EN ISO 24342	Avg±0.1mm, Max≤0.2mm	
Tolerance on the squareness	EN ISO 24342	side length≤400mm, squareness≤0.25mm	
		side length > 400mm, squareness≤0.35mm	
Thickness	EN ISO 24346	6.5mm (+/-0.15mm)	
Wear Layer Thickness	EN ISO 24340	0.5mm (+/-0.05mm)	
Determination of stability	EN ISO 23999	≤ 0.15%	
Curl resultant to heat	EN ISO 23999	≤ 1mm	
Color fastness	EN ISO105-B02	6 class	
Reaction to Fire	EN 13501-1	Bf1-S1	
Castor Chair Resistance	EN 425	Pass	
Peeling strength of layer	EN431	≥ 95N/5cm	
Locking strength	ISO 24334	Long-side: ≥150N/5cm	
		Short-side: ≥150N/5cm	
Stain Resistance	EN423	Not affected	
VOC	ISO 16000	VOC A+	
Slip Resistance	DIN51130	Class R9	
Residual Indentation	ISO24343-1:2007	≤0.1mm	
Chemical Products Resistance	EN423	Pass	
Ortho-Phthalates	US EPA 3550c:2007	None	
PCP	EN 12673	None	
Formaldehyde Emission	EN717-1	E1	